



## OZZ X01 P

Experience the power of light with OZZ X01 P LED oval auxiliary lights. These 245 mm lights feature dynamic start-up position light in white and orange, adding a visually stunning effect during ignition. It also offers an integrated warning light in two different flash patterns; single and double. With a brightness of 5100 lumens and 1 lux reaching up to 475 meters, these lights provide optimal visibility. The driving beam pattern ensures a wide and long-range reach. With a color temperature of 5000 K, it offers pleasant illumination in all conditions.

|                                |                                |
|--------------------------------|--------------------------------|
| <b>Art. no.</b>                | 88106 (white)                  |
| <b>Lamp type</b>               | LED                            |
| <b>Diodes</b>                  | 8 pcs                          |
| <b>Voltage</b>                 | 10-35V DC                      |
| <b>Actual effect 12V</b>       | 95 W                           |
| <b>Actual effect 24V</b>       | 95 W                           |
| <b>Nominal current at 12V</b>  | 7.2 A                          |
| <b>Nominal current at 24 V</b> | 3.6 A                          |
| <b>Theoretical lumen</b>       | 8160                           |
| <b>Actual lumen</b>            | 5100                           |
| <b>1 lux @ (m)</b>             | 475                            |
| <b>Kelvin (K)</b>              | 5000                           |
| <b>IP-class</b>                | IP68/IP69K                     |
| <b>Beam pattern</b>            | driving                        |
| <b>Position light</b>          | dynamic white & amber          |
| <b>Connection</b>              | 6-pin DT male+female (1000 mm) |
| <b>Functions</b>               | High beam, amber warning light |
| <b>Material chassi, lens</b>   | aluminum, polycarbonate        |
| <b>LxDxH (mm)</b>              | 245x90x140/162,5               |
| <b>Operating temperature</b>   | -40 - +60°C                    |
| <b>E-mark approval</b>         | R112, R7, R65                  |
| <b>EMC</b>                     | ECE R10                        |
| <b>Ref. no.</b>                | 50                             |
| <b>Weight (kg)</b>             | 1,95                           |
| <b>Warranty</b>                | 3 years                        |

