

## **OZZ XR**2 **P**9"

Experience the power of light with OZZ XR2 P9". These 220 mm lights feature a dynamic start-up position light in white and orange. The innovative successor to the original OZZ light series offers a new prominent start-up pattern for an impressive visual effect upon ignition. With a boost function, the OZZ XR2 P9" emits 10 600 lumen, providing 1 lux at a distance of 680 meters. The driving beam pattern ensures optimal visibility with a wide and long-range reach. The lights have a color temperature of 5000 K, offering pleasant illumination in all conditions.

Art. no.	88101 (black)		81.3	
Lamp type	LED	\$220.		
Diodes	16 pcs			ATTINA
Voltage	10-35V DC			
Actual effect 12V	R112: 74 W, boost: 134 W	-((	0 00 00 00 00 00 00 00 00 00 00 00 00 0	-4
Actual effect 24V	R112: 73 W, boost 130 W			8-1114111-B
Nominal current at 12 V	10.5 A			
Nominal current at 24 V	5.2 A			-ddillap-
Theoretical lumen	15000	M10	• /	1
Actual lumen	R112: 7010, boost: 10600			
1 lux @ (m)	R112: 480, boost: 680			
Kelvin (K)	5000			
IP-class	IP68/IP69K	45m 5561 x	101x	11x
Beam pattern	driving	30m		
Position light	dynamic white & amber			
Connection	4-pin DT male+female (1000 mm)	15m		
Material chassi, lens	aluminum, polycarbonate	Om Com		
ØxDxH (mm)	220×84,3×210/227	-15m		
Operating temperature	-40 - +60°C	-30m		
E-mark approval	R112, R7	-45m		
EMC	ECE R10	25m	215m	680m
Ref. no.	50			
Weight (kg)	2,6			
Warranty	3 years			

