



## OZZ XR2 P9" Driving light LED - White

Experience the power of light with OZZ XR2 P9". These 220 mm lights feature a dynamic start-up position light in white and orange. The innovative successor to the original OZZ light series offers a new prominent startup pattern for an impressive visual effect upon ignition. With a boost function, the OZZ XR2 P9" emits 10 600 lumen, providing 1 lux at a distance of 680 meters. The driving beam pattern ensures optimal visibility with a wide and long-range reach. The lights have a color temperature of 5000 K, offering pleasant illumination in all conditions.

<b>Art. no.</b>	88102	<b>Connection</b>	4-pin DT male + female
<b>Pcs LED</b>	16	<b>Cable length (mm)</b>	1000 (800+200)
<b>Voltage</b>	10-35V DC	<b>Material bracket</b>	Stainless steel
<b>Theoretical effect</b>	160W	<b>Material housing</b>	Aluminum
<b>Actual effect</b>	R112: 74W, boost: 134W (12V DC), R112: 73W, boost: 130W (24V DC)	<b>Material lens</b>	Polycarbonate
<b>Nominal current</b>	R112: 6,12A, boost: 11,17A (12V DC), R112: 3,04A, boost: 5,42A (24V DC)	<b>Lenght (mm)</b>	220
<b>Functions</b>	High beam, Boost mode, Dynamic position light	<b>Depth (mm)</b>	84,3
<b>Theoretical lumen</b>	15000	<b>Height (mm)</b>	210
<b>Actual lumen</b>	R112: 7010, Boost: 10600	<b>Height including bracket (mm)</b>	227
<b>1 lux @</b>	R112: 480 m, Boost: 680 m	<b>Diameter (mm)</b>	220
<b>Kelvin</b>	5000K	<b>CC (mm)</b>	-
<b>IP-class</b>	IP68/IP69K	<b>Operating temperature</b>	-40°C - +60°C
<b>Beam pattern</b>	Driving	<b>E-mark approval</b>	ECE R148, R149
<b>Position light</b>	Dynamic white and amber	<b>Reference number</b>	50
<b>Color housing</b>	White	<b>EMC</b>	ECE R10
<b>RAL color</b>	RAL9003	<b>Pcs in master box</b>	4
<b>Color lens</b>	Clear	<b>EAN</b>	7333213101442
<b>Color LED</b>	White, amber	<b>Warranty</b>	3 years

